

Ultranitril 492

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (cm)** 32
- **Thickness (mm)** 0.38
- **Wrist** Straight cuff
- **Colour/Color** Green
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10 11
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton
- **Complementary information** Guaranteed without silicone
available in 2 kind of packaging : individual bag and polybag of 10



PERFORMANCE RESULTS

Certification category 3

CE 0334



AJKL

4101

Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
Abrasion resistance
Blade cut resistance
Tear resistance
Puncture resistance



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
Burning behaviour
Contact heat resistance
Convective heat resistance
Radiant heat resistant
Resistance to small drops of molten metal
Resistance to large quantities of molten metal



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**RADIOACTIVE
CONTAMINATION
EN 421**



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
Convective cold resistance
Contact cold resistance
Water permeability

For more details: www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining
- Longer service life: excellent mechanical resistance (abrasion, perforation)

MAIN FIELDS OF USE

Automotive/mechanical industry

- Treating/degreasing metals with solvents
- Machining parts using cutting oil

Local Authorities (Cleaning)

- Handling aggressive chemical products

Construction Industry (Carpenters/Joiners)

- Handling PVC-based glues
- Preparing coatings, varnishes

Construction Industry (Masons / Plasterers)

- Handling oils, solvents, detergents

Local Authorities (Parks and Public Spaces)

- Plant Treatment Products

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Persons sensitised to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service • MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging protected from light, humidity and heat.

Laundering conditions

Before taking off the gloves, clean them as appropriate : • in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth • in use with a solvent (dilutents, etc...) : rub over with a dry